

PTF Thickener

General
Thickener

Advantages

- PTF Thickener viscosity capability is perfect even if small quantities therefore it should be tried in pastes.
- It protects to alive of pigments.
- Suitable to ecological standards.

Applications

- Before usage, please stir the product well.
- Do not use any additives that are not advised.
- Never use water to reduce the viscosity.
- After using, the silk-screen should be cleaned with water.

Usage

- PTF Thickener provides to raise of viscosity of print paste and liquids which has pH 7 and above.

Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30)°C /(+41)-(+86)°F of temperature.
- It should be consumed within 2 years after the production date.

Technical Details



Appearance
Viscous Liquid



Odor
Characteristic



Color
Yellowish



Viscosity
[(25 °C/77 F) sp: 2, rpm: 20 Brookfield] :
1.000 – 1.200 [mPa.s]



Density
1,17 g/cm³ (77°F / 25°C)



pH
6,0 – 7,5



Boiling Point
>100°C (212°F)



Solubility
N/A



Explosion Hazard
Not explosive



Packaging Information
PTF Thickener is packed in
1/5/10/20/30/60 kg plastic cans.

Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.