

D 40

General

A retarder for water based products. Provides long working time and blocks early curing on hot screens.

Advantages

- D 40 increases all fastness of products which mixing it.
- Non-clogging
- Eliminates blocking and improves softness
- Increases print performance
- Suitable to ecological standards.

Applications

- It prevents the processed paste from drying during printing and clogging in the mold.

Usage

- D 40 prevents to dry & blocking of the operated paste in the silk-screen.

Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30)°C /(+41)-(+86)°F of temperature.
- It should be consumed within 2 years after the production date.

Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.

Technical Details



Appearance
Paste



Odor
Characteristic



Color
Transparent



Density
1,11 g/cm³ (77 °F/25°C)



pH
6,0 – 7,0



Boiling Point
>100°C (212°F)



Solubility
Soluble in water



Explosion Hazard
Not explosive



Packaging Information
D 40 is packed in 1/5/10/20/30/60 kg plastic cans.